

# TB 100-C

**CIPPATORE CINGOLATO  
(PER RAMI FINO A 9 CM)**  
**TRACKED WOOD CHIPPER  
(FOR BRANCHES UP TO 9 CM)**

Il cippatore TB100-C è una macchina robusta e di compatte dimensioni, utilizzata per ridurre scarti vegetali, per uso privato o professionale, da 5 a 10 m<sup>3</sup>/ora. Destinata al taglio sia di rami secchi che umidi da 6 fino a 9 cm di diametro, viene principalmente utilizzata da utenti privati, noleggiatori, giardinieri ed enti pubblici.

Dotata di due lame temperate reversibili a doppio tagliente, con sistema no-stress di serie e grazie al design del suo rotore, la macchina lavora rami, ramoscelli e talee senza esitazione, trascinandole all'interno della bocca di taglio senza la necessità di disporre di un apposito rullo di trascinamento. La forza centrifuga creata dal rotore espelle il materiale tritato in maniera fine, proiettandolo fuori dallo scarico (girevole e orientabile in altezza) a circa 3/5 mt di distanza (a seconda del prodotto), consentendo un facile caricamento in presenza di appositi contenitori o su rimorchi. Le compatte dimensioni di ingombro e i cingoli (mossi da motore indipendente da 4 CV), ne consentono l'utilizzo anche in zone anguste o terrazzamenti, oltre al facile carico su piccoli furgoni grazie all'ausilio di apposite rampe. Prodotto negli stabilimenti Peruzzo questo cippatore è mosso da motore a scoppio da 18 CV e può diventare, in poche semplici mosse, un'agile moto-carriola (accessorio a parte) utile per il trasporto di legna e altro materiale.



*The TB100-C tracked chipper is a robust and compact machine, used to reduce vegetable waste, for private or professional use, from 5 to 10 m<sup>3</sup>/hour. Intended for cutting both dry and wet branches from 6 to 9 cm in diameter, it is mainly used by private users, charterers, gardeners and public bodies.*

*Equipped with two reversible tempered blades with double edge, with no-stress system as standard and thanks to the design of its rotor, the machine works branches, twigs and cuttings without hesitation, dragging them inside the cutting area without the need to have a special drag roller. The centrifugal force created by the rotor ejects the shredded material in a fine way, projecting it out of the outlet (swivel and adjustable in height) about 3/5 meters away (depending on the product), allowing easy loading in the presence of special containers or on trailers. The compact dimensions and the tracks (driven by an independent 4 HP engine), allow it to be used even in cramped areas or terraces, in addition to easy loading on small vans thanks to the help of special ramps. Produced in Peruzzo factories, this chipper is powered by an 18 HP internal combustion engine and can become, in a few simple steps, an agile wheelbarrow (separate accessory) useful for transporting wood and other material.*




MODELLO MODEL	CAPACITÀ DI TAGLIO CUTTING WIDTH (CM)	BRAND E POTENZA MOTORE - BRAND & ENGINE POWER (HP / KW)	QUANTITÀ LAME BLADES QUANTITY
TB 100 - C (Cingolato-Tracks)	9	18 / 3,5 - 13 / 2,6	2



**COMPONENTI TECNICHE**  
**TECHNICAL COMPONENTS**



3 marce + retromarcia.  
3 gear + reverse.



Tamburo cippatore (300 mm x 150 mm).  
Chipping drum (300 mm x 150 mm).



Curva di scarico orientabile a 360°.  
360° adjustable outlet elbow.



Pianale porta attrezzi (portata 350 kg).  
Tool platform (capacity 350 kg).



**LAME STANDARD**  
**STANDARD BLADES**

Lama cippatrice fissata con viti a testa esagonale.  
Chipping blade fixed with hexagonal head screws.



MODELLO MODEL	PESO WEIGHT (KG)	 (LxPxH)	DIMENSIONI IMBALLAGGIO PACKAGING DIMENSIONS (LxPxH)
TB 100 - C (Cingolato-Tracks)	350	2160 x 695 x 1710	1600 x 800 x 1800